



Boydur® A10

MMA BASED, SOLVENT FREE, ONE COMPONENT,
TRANSPARENT, SURFACE PROTECTION AND

Boydur® A10 is a one-component solvent free resin. It is used for surface protection and for primer application. Boydur® A10 can also be used as a primer of flooring and road marking paint applications.(e.g. Boydur® Akrifleks, Boydur® Marker 564.etc)

Advantages:

- One component, MMA based
- It protects the surface against ageing, UV. and weather conditions.
- Fast curing period (approx.: 1 hour),
- Long Lasting ,
- Very good connection with surface, impregnated,
- Anti-bacterial, easy to use,
- Increased the quality of the surface appearance.

Where to Use: All kind of industrial Areas, Airports, Seaports, Refineries, Military Areas, Business and Shopping centers, Hospitals, Conference Halls, Exhibition Centers, Car parks, Houses, Apartments, Sidewalks

Technical Features:

Form: Liquid

Color: Transparent

Use: ~ 200-300 gr./m²

Curing (20 °C): ~ 1 Hour

Min. Application Temperature: 10 °C

Storage: 6 months in dark, dry, room temperature

Packages: 15 Kg.

P.S: Boydur® A10 can used over Concrete, Asphalt and Mosaic floor surfaces.

Application: (For more information www.boytorun.com)

- The surface must be clean, dry and in condition. Do not apply, if the surface is not in good condition.
- If the surface is new, wait for solidification period (e.g. 28 days for cement).
- Do the application with brush, roller or spray machine. It dries in 1 hour.
- If it is necessary, apply a second layer.

