



Boydur® A125

MMA Based, Solvent Free, Two Components, Elastic, Quick Repair And Filler Mortar

Boydur® A125 is a two components, MMA based, solvent free, elastic, quick repair and filler mortar. It is suited for inside and outside areas. It is specially used on the area, where elastic filler necessary is. Boydur® A15 and Boydur®A125 are used for the same aims. The only difference is the elasticity. Boydur® A125 is more elastic than Boydur® A15.

Advantages:

- MMA based, Two components Solvent free,
- Fast curing period (approx.1 Hour),
- Long lasting, Easy to use, easy to repair,
- Full resistance against UV and all weather conditions,
- Full resistance for heavy load, many chemical materials,

Where to use?: Airports, seaports, Industrial areas, All types of military areas, Business centers, shopping centers, Roads, highways, Bridges, Parks.

Technical Features:

Delivery Form: Liquid

Color: Grey, Red, Green, Black

Viscosity: 4500-5000 mPa.s

Density: 1, 20 gr./cm³

Drying Period (20 ° C): ~ 1 Hour

Application Time (after mixing A+ B Components): ~ 25 minutes

Storage: 6 months in dark, dry, room temperature

Packages: 25 Kg.

Application: (Details in www.boytorun.com)

- Be sure that the surface is in correct condition for application.
- Apply Boydur® A10 with brush and roller. It dries in 1 hour.
- Mix Boydur® A125 with approx. % 1 of Boydur Herter hardener homogenously for approx.2-2, 5 minutes
- Throw it on the surface, where Boydur® A10 already applied. Help with trowel to spread it. It dries in 1 Hour.
- Clean the application tools with Boydur® S90.

