

## Safety Data Sheet

### Boydur® Akribeton

Identification of the substance/ preparation and of the company undertaking:  
Product Information: Boydur® Akribeton, two components, MMA based  
Polymerbeton

#### Information About The Manufacturer:

Boytorun Kimya Sanayi A.S.

İ.E.T.T. Sitesi,3. Blok,D:1, Emirgan- 34467- Istanbul- TR.

Emergency Call: 0090-212- 229 18 29- 2 29 18 34

Fax 0090-212-229 18 59, E-Mail: info@boytorun.com

#### Information Of Ingredients:

Chemical properties:

MMA Based, Solvent Free, Two Components, Quick Repair and Anchorage  
Polymerbeton

Cas No: 80-62-6

Index No: 607-035-00-6

EEC No: 201-297-1

#### Hazards Identification:

Description of Dangers

F Higly flammable Xi Irritant

Special guidelines concerning dangers to humans and the environment

When heated, formation of explosive vapour / air mixtures

Danger of bursting of closed systems to vigorous exothermic polymerization. Avoid uncontrolled polymerization.

n.a= not applicable; n.d.= not defined; \* = change

## Boydur® Akribeton

### First- aid measures

- General information

Bring affected persons out of danger area.

Remove contaminated or saturated clothing immediately.

- **Following inhalation:**

Bring affected person outside and ensure that he/sh is comfortable.

Employ artificial respiration if breathing cases.

Supply with medical care.

- **Following contact with skin**

On skin contact, rinse thoroughly with water and soap

With Continuous skin irritation, consult doctor.

- **Following eye contact:**

Rinse thoroughly immediately with plenty of water for at least 5 minutes keeping eyelid open.

Further treatment by eye doctor.

- **If substance has been swallowed**

Consult doctor immediately.

- **Instructions for the doctor**

Following inhalation

Beta methasone dosage aerosol spray

Paraffinum subliquidum

Fire-fighting measures

- **Suitable extinguishing substances**

Mist, quenching foam, quenching powder, carbon dioxide.

- **Unsuitable extinguishing substances**

Water, full jet

- **Particular danger caused by material, its combustion products or gases produced**

In case of combustion or decomposition of the product, the fumes produced lead to irritations or inflammations of the respiratory tract.

Formation of flammable or explosive vapour / air mixtures possible.

Usual measures for chemical fires.

Fire residues should be disposed of in accordance with the regulations.

## Boydur® Akribeton

Water used to extinguish fire should not enter drainage systems, soil , or stretches of water.

- **Special protective equipment**

In the case of fire, wear respiratory protective equipment independent of surrounding air and chemical protective suit. In case of fire cool containers or take them to a safe place. danger of polymerization.

### Accidental release measures

- **Personal precautionary measures**

Keep persons at a distance and stay on the weather side. Wear personal protective equipment; see section 8. Avoid contact with Product.

- **Measures for environmental protection:**

Do not allow entrance in sewage water stretches of water drainage systems.

- **Procedure for cleaning / absorption**

Remove all sources of ignition.

Ensure explosion proof ness.

Isolate and seal of f defective containers immediately. ( check, dam up, cover up)

Absorb with liquid-binding material (e.g. inert absorbent sand universal binder)

Absorb mechanically with suitable device and collect in a suitable container.

### Handling and storage

- **Handling**

Always close container tightly after removal of product.

Protect from contamination heat sun rays.

Keep away from sources of ignition- No Smoking

- **Directions for safe Handling**

Product is supplied in stabilized form.

Stir and shake well before use.

Open container carefully as it may be pressurized.

Local ventilation if necessary.

## Boydur® Akribeton

- **Directions on fire and explosion safety**

Highly flammable

Caution- electrostatic charge may occur.

Keep away from sources of ignition. Do not smoke.

danger of explosion.

Water used to extinguish fire should not enter drainage systems, soil, or stretches of water.

Ensure there are sufficient retaining facilities for water used to extinguish fire.

Contaminated fire extinguishing water must be disposed of in accordance with the regulations issued by the appropriate local authorities.

Fire residues should be disposed of in accordance with the regulations.

Explosion- proof installations required.

- **Storage**

Keep container tightly closed and store in a dry, well- ventilated place. Storage capability limited; dependent on Storage temperature.

Maximum storage period: 6 Months

- Requirements for storage rooms:

Ensure there is good room ventilation.

Maximum storage temperature: 25 o C

Exposure controls / personal equipment

- **Additional directions on design of technical equipment**

Ensure suitable suction /aeration at the work place and with the operational machinery.

- **Components with work place related limits to be monitored**

Name of substance: Methyl methacrylate

Cas- No: 80-62-6

Index-No: 607- 035- 00-6

Limits Values Unit

Methyl methacrylate

Mel (GB) 100 ml/ m<sup>3</sup> = 410 mg/ m<sup>3</sup> ( 1993)

TLV/TWA (USA) 100 ml/ m<sup>3</sup> = 410 mg/ m<sup>3</sup> (1993)

## Boydur® Akribeton

- **Personal protective equipment**

Measures for general protection and hygiene

No eating' drinking' smoking, or snuffing tobacco at work.

Wash face and / or hands before break and end of work.

If the limits at the workplace are exceeded and / or larger amounts are released ( leakage, spilling, etc.) the indicated respiratory protection should be used.

Avoid contact with skin and eyes.

If there is the possibility of skin/eye contact the indicated hand/eye/body protection should be used.

- **Respiratory protective equipment:**

If workplace exposure limit is exceeded apply Respiratory protective equipment independent of surrounding air.

- **Hand protection:**

Wear protective gloves made of latex or rubber

- **Eye Protection:**

Basket-shaped glasses

- **Body Protection**

Protective clothing, antistatic and flame resistant

Change work clothes that have been moistened or saturated with product.

## Physical and chemical properties

### Description:

Boydur® Akribeton is a two components, MMA based Polimerbeton. It is suited for inside and outside areas. It can be used as a quick repair material for hole and cracks, which causes dangerous situation on the areas with heavy traffic and chemical resistance. It is mainly used as a quick repair mortar, for the areas in where cracks and holes cause a dangerous situation

### Properties:

Boydur® Akribeton is highly is resistant to chemicals

Boydur® Akribeton

**Characteristic data:**

Form supplied	17 kg. A+ B component
Hardening period	30-35 minutes
Compressive Strength	75 N/mm <sup>2</sup>
Bending strength	26 N/ mm <sup>2</sup>
E- Modul	4350 N/mm <sup>2</sup>
Ball Impact hardness	43 N/mm <sup>2</sup>
Flash point	DIN 51755,+110C ( Resin Material)
Shelf life, dark at<200C	min. 6 months

- **Stability and reactivity**

Danger of bursting of closed systems to vigorous exothermic polymerization. Avoid uncontrolled polymerization.

- **Conditions to be avoided**

Product polymerizes on contact with radical generating substances such as peroxides, azo compounds, heavy metal compounds and solutions.

- **Additional guidelines:**

Product is supplied in stabilized form.

Toxicological information

No results of animal experiments with this preparation are available.

The following data refers to the subsequently named constituents.

Methyl methacrylate

Acute oral toxicity; LD 50= 7872 mg/ kg, rat, literature

Acute dermal toxicity: LD 50> 9 400 mg/ kg, rabbit, literature

Acute inhalation toxicity: LC 50= 29.5 mg/1/ 4h, rat, literature

Primary irritative effect to skin: non-irritative, rabbit, OECD 404

- **Further Information**

Following years of experience, upon proper handling no detrimental effects have become known.

Boydur® Akribeton

### Ecological data:

No ecotoxicological studies are available.

The following data refers to the subsequently named constituents.

Methyl methacrylate

Environmental hazard

Classification by Federal Environmental Agency ( Germany): group III

“ Material with, based on current knowledge’ low potential for hazard.”

- **Data on elimination (Persistence and degradability)**

Methyl methacrylate

Degradation (28 Days)= 33.7 %, not easily biodegradable, OECD 301 C.

- **Behavior in environmental fields**

Air contamination causes unpleasant odour.

Methyl methacrylate Odour threshold: 0.5 until 5 mg/ m<sup>3</sup>

- **Eco-Toxic effect Methyl methacrylate**

Bacterial toxicity:

Pseudomonas putida, initial inhibition of cell multiplication at > 100 mg/l, evaluation of water-pollutive substances; UBA

- **Aquatic toxicity:**

Acute fish toxicity: LC 50 ( 48 h ) = 350 mg/ l, Leuciscus idus melanotus, literature.

### Disposal Considerations

- **Product**

#### Recommended

Must be brought to an authorized special waste incineration plant in accordance with the regulations on special waste following according to local regulations. European waste catalogue(EWC)

07 02 99: Wastes not otherwise specified

Can be disposed of with domestic refuse following polymerization in accordance with the necessary technical regulations following consultation with waste disposal expert(s) and the responsibly authorities,

European waste catalogue ( EWC)

17 02 03: Plastic

Bring decontaminated packaging to local recycling center

Boydur® Akribeton

- **Recommended cleaning agent**

Acetone,

Ethylacetate

Transport Information

Dangerous according to the transport regulations

GGVS/ GGVE/RID/ADR/ IMDG Code/ ICAO-TI

yes

Surface transport ADR/ RID/ GGVS/ GGVE

Classification

Class 3 Number 3 Letter b)

Danger Labels

No 3 (2) No (3) No (4) No

Orange warning plate 339/1247

Listed good according to art 7 GGVS no

Listed good according to art 7 aGGVS no

Accident data sheet Rail 30.039

Name of product ( proper shipping name surface transport) contains methyl methacrylate ' stabilized

Loading instructions/ comments

- **Road ( National)**

Measures a sper marginal note 2300 (6) GGVS/ADR and 300 (6) GGVE/RID have been applied.

- **Road (International)**

Measures a sper marginal note 2300 (6) GGVS/ADR and 300 (6) GGVE/RID have been applied.

- **Rail (National)**

Measures a sper marginal note 2300 (6) GGVS/ADR and 300 (6) GGVE/RID have been applied.

- **Rail ( International)**

Measures a sper marginal note 2300 (6) GGVS/ADR and 300 (6) GGVE/RID have been applied.



## Boydur® Akribeton

Transport by vessel IMDG Code /GGVSee  
Clasification

Class 3.2 Un- No 1247 Packagng Group II

Danger Labels

Label 3 Label(2) Label (3) Label(4)

Danger of water Pollution

Emergency action

EmS 3-07 EmS (2)

MFAG 330 MFAG (2)

- Proper Shipping Name

Methylmethacrylate, monomer, inhibited, solution

Remarks

Keep away from accomodation and communal rooms.

- Air Transport ICAO-TI/IATA-DGR

Classification

Class 3 Un-No 1247 Packaging Group II

Danger Labels

Label 3 Label (2) Label (3) Label (4)

- Proper Shipping Name

Methylmethacrylate, monomer, inhibited, solution

Remarks

Drill 3L

- Inland Navigation ADN/ADNR

The transport classification for inland navigation has not yet been determined; please consult us before shipment is necessary.

## Regulatory Information

Labelling of preparation in line with EC Directive (in accordance with supplement II of directive on preparations 88/379/EEC)

Boydur® Akribeton

- **Index Letter and indication of danger posed by product**

F Highly flammable

Xi Irritant

- Hazardous component(s)

Methylmethacrylate

- **R-phrases**

R 11-36/37/38-43

Highly flammable

Irritating to eyes, respiratory system and skin.

May cause sensitization by skin contact.

- **S- Phrases**

S 9-16-29-33

Keep Container in a well-ventilated place.

Keep away from sources of ignition-No smoking.

Do not empty into drains.

Take precautionary measures against static discharges.

If preparation is freely available ( public product) , the following additional safety advise is required.:

S2

Keep out reach of children

- **National Regulations**

Observe national regulations.

**Other Information:**

Further information on properties and safe handling of product can be obtained from the product brochures.

Boytorun Kimya Sanayi A.S.

İ.E.T.T. Sitesi,3. Blok,D:1, Emirgan- 34467- Istanbul- TR.

Emergency Call: 0090-212- 229 18 29- 2 29 18 34

Fax 0090-212-229 18 59, E-Mail: info@boytorun.com