



Boydur® Akrigum

MMA BASED, TWO COMPONENTS, ELASTIC, QUICK REPAIR AND JOINT FILLER

Boydur® Akrigum is a two components, MMA based, quick repair and Joint filler. It is suited for inside and outside areas.

Advantages:

- MMA based,
- Solvent free, long lasting.
- Two components.
- Used on the surface, where Boydur® A10 applied,
- Fast curing period (approx.1. Hour),
- Easy to use,
- Full resistance against UV and weather conditions.

Where to Use: All kind of industrial Areas, Airports, and Seaports, Refineries, Military Areas, Business and Shopping centers, Hospitals, TV Studios, Conference Halls, Exhibition Centers, Car parks

Technical Features:

Delivery Form: Liquid

Color: Grey, Red, Green, Black

Viscosity: 4500-5000 mPa.s

Density: 1,00 gr./cm³

Drying Period (20°C): ~ 1 Hour

Application Time (after mixing A+ B Components):
~ 25 minutes.

Storage: 6 Months in dark, dry, room temperature

Packages: 20 Kg.

Application: (For more information www.boytorun.com)

- The surface should be dry, clean and in good condition.
- Use Boydur® A10 before Boydur® Akrigum application.
- Be sure that the surface is in correct condition for application.
- Apply Boydur® A10 with brush and roller. It dries in 1 hour.
- Mix Boydur® Akrigum with Boydur Herter hardener homogenously for approx.2-2, 5 minutes (see the Boydur® Herter Hardening Time Table).
- Throw it on the surface, where Boydur® A10 already applied. Help with trowel to spread it. It dries in 1 Hour.
- Clean the application tools with Boydur® S90.

