



Boydur® Boycolor

MMA Based, One Component, Surface Protection Paint

Boydur® Boycolor is a MMA based, one component, surface protection paint mainly used on outside areas. It is full resistance against UV. and all types of weather conditions. It is also used in inside areas, especially where anti-bacterial wall surface is necessary.

Advantages:

- MMA based, One component,
- Fast curing period (Approx: 1 hour),
- Long lasting (e.g. over cement 10 years quality guarantee),
- Very good connection with surface, impregnated,
- Produce in different RAL Colors,
- Resistance to UV. and all types of weather conditions,

Where to use? Military areas, Houses, Villas, Apartments, Factories, Business centers, Airports, Seaports, Dockyards, Shopping centers, Car parks,

Technical Features

Delivery Form: Liquid

Main material: MMA

Color: Different RAL colors

Use: ~ 300-400 gr./m²

Curing (20°C): ~ 1 Hour

Min. Application Temperature: 10°C

Storage: 6 months in dark, dry, room temperature

Packages: 20 Kg.

Thinner: Boydur® S45 in 9 kg. packages.

Application (Details www.boytorun.com)

- The surface must be clean, dry and in condition. Do not apply, if the surface is not in good condition.
- If the surface is new, wait for solidification period
- Use Acrylic base repair filler for fixing the cracks of the wall.
- Mix % 10 of Boydur® S45 thinner with Boydur® Boycolor and apply it as a primer level. It dries in 1 hour.
- If it is necessary use the second level with % 5 of Boydur® S45. It dries in 1 hour.
- Clean your application tools with Boydur® S90.

