



Boydur® CK 100

MMA Based, One Component, Solvent Based, Surface Paint

Boydur® CK 100 is a MMA based, one component, surface paint. It is easy to use in inside and outside areas.

Special features and Advantages:

- MMA based, One component,
- Easy to use, Easy to repair,
- Fast curing period (approx: 1 hour),
- Full resistance against UV. and all types of weather conditions.
- Resistance to dirt, oil, etc.,
- Thermoplastic flexibility,
- Safety application,

Where to Use?:

- For coating cement or asphalt sport fields,
- Sidewalk, Bicycle ways,
- Industrial areas, which have light traffics,
- Military areas,
- Airports and seaports, Stadiums,
- Shopping centers, business centers,
- Houses, villas, apartments.

Technical Features:

Delivery Form: Two components, fluid (A+ B components)

Color: Grey, Red, Green, Black

Use: 2000 kg. /m³

Compressive strength: 34 N/mm²

Bending Strength: 24 N/mm²

E-Module: 4350 N/mm²

Ball Impact Hardness: 41 N/mm²

Drying Period (20 °C): ~ 1 Hour

Application Time (after mixing A+ B Components): ~ 25 minutes.

Storage: 12months in dark, dry, room temperature (Without opening the package)



Application: (Details: www.boytorun.com)

- Mix 10% of Boydur® S45 thinner with Boydur®
- CK100 and apply it as a primer level. It dries in 1 Hour.
- If it is necessary apply the second level with 5% of Boydur® S45. It dries in 1 hour.
- Apply Boydur® CK100 with roller. It dries in 1-2 hour.
- Clean the application tools with Boydur® S90.