



## Boydur® H900

MMA BASED, SOLVENT FREE, AIR-DRIED,  
TRANSPARENT, SURFACE PROTECTION AND PAINT  
PRIMER RESIN

Boydur® H900 is a one component solvent free resin, used for surface protection. It is suited for inside and outside areas. It protects the surface against ageing, UV and all types of weather conditions. Boydur® H900 can also be used as a primer of paint.

### Advantages:

- One component, MMA based
- Fast curing period,
- Long lasting period (Approx. 1 hour after the application).
- Long Lasting (e.g. over cement 10 years quality guarantee),
- Very good connection with surface, impregnated,
- Anti-bacterial,
- Easy to use,
- Resistance to UV. and all types of weather condition,

**Where to Use:** In old buildings (mosques, churches, structures, columns, temples, structures, etc.), Airports, Seaports, Military Areas, Houses, Villas, Apartments, Factories, Roads, Sidewalks, Bars, Restaurants.

### Technical Features:

Form: Liquid  
Color: Transparent  
Use: ~ 200-300 gr. /m<sup>2</sup>  
Curing (20°C): ~ 1 Hour  
Min. Application Temperature: 10°C  
Storage: 6 months in dark, dry, room temperature (20°C)  
Packages: 15 Kg.

### Application: (For more information [www.boytorun.com](http://www.boytorun.com))

- The surface must be clean, dry and in condition. Do not apply, if the surface is not in good condition.
- If the surface is new, wait for solidification period (e.g. 28 days for cement).
- Do the application with brush, roller or spray machine. It dries in 1 hour.
- If it is necessary, apply a second layer.

