



Boydur® Marker 100

MMA Based, One Component, Cold Plastic, Road Marking Paint

Boydur® Marker 100 is a MMA based, one component road marking paint. It can apply outside and inside areas.

Advantages:

- Fast curing period (Approx.: 1 hour after the application)
- MMA Based, one component, produce with RAL traffic colors.
- Full resistance to UV. and all types of weather conditions
- Easy and safe to apply.
- Resistance to dirt, oil, etc.
- Thermoplastic flexibility, excellent night vision.

Where to Use: Industrial areas – Car Parks – Storage Areas - Airports - Ports - Shipyards – Military Areas – City and Intercity Roads – Exhibition Centers - Bridges-Side Walks- Schools- Sport Fields

Technical Features:

Delivery Form: Liquid

Main Material: MMA

Curing Period (at 20 ° C): Approx 1 hour after the application

Colors: Different RAL Colors

Density: 1,56 Kg./Lt.

Layer Thickness: 0,5-1,2 mm.

Use: 500 gr/m²

Color Index: APHA < 50

Storage Life (20° C): Max. 6 months (not under the sun, in dry conditions)

Package: 25 Kg.

Thinner: Boydur® S45. Mix % 10 of thinner inside of the paint.

Application: (For more information www.boytorun.com)

- The surface should be dry, clean and in good condition.
- Use MMA based mortar to repair cracks and holes.
- Boydur® Marker 100 can be applied easily with brush, roller or airless spray machine.
- Mix %10 of Boydur® S45 thinner with Boydur® Marker 100 and apply it as a primer level. It dries approx. in 1 hour.
- If it is necessary apply the second level with % 10 or less thinner.

